



PP 短纤维无纺布工艺生产并加驻静电使其满足空气过滤要求: PP staple fiber mat with electrical charge for air filtration:

滤效等级 | Efficiency: F5-H11 (45% - 95%) 阻力 | Pressure Drop: 2-6 Pa

- 应用市场:暖通空调、汽车空调滤芯、空气净化器等
  Applications: Air conditioner, Automotive cabin air, Air purifier and etc.
- 产品优势 | Advantages:

性价比高;可与不同基材复合。 Cost effective; Can be combined with different backing layer materials. 阻力低,容尘量高,使用寿命长。 Low pressure drop, high duct holding capacity and strong durability.

Туре	Area Weight (g/m²)	Thickness (mm)	Initial Efficiency* (%)	Pressure Drop (Pa)	Structure	Max. Width (mm)	Max. Roll Length (m)
JK-D45%	50 ±10	$0.90\pm0.1$	≥45	≤2	PP Cotton + PP protective layer	1500	250
JK-D65%	50 ± 10	$0.90 \pm 0.1$	≥65	≤3			
JK-D90%	70 ±10	$1.1 \pm 0.1$	≥90	≤4			
JK-D95%	80 ±10	1.15 ± 0.1	≥95	≤4			
JK-PD45%	110 ±10	$1.05 \pm 0.1$	≥45	≤4	PP protective - layer + - PP Cotton + PET backing layer	1500	250
JK-PD65%	110 ±10	$1.05 \pm 0.1$	≥65	≤5			
JK-PD90%	130 ±10	1.3 ± 0.1	≥90	≤6			
JK-PD95%	140 ±10	1.35 ± 0.1	≥95	≤6			

## 产品技术参数 | Product Technical Data

\* 测试条件 | Testing condition: 0.3µm NaCl @ 5.3cm/s

基材可按客户要求定制。| Backing layer material can be customized according to requirement from customers.

## 免责声明/Disclaimer

。 该资料中产品的公开性能参数不属于对产品质量具有法律约束力的声明。 这些性能参数不会成为合同的组成部分。它们代表在制造时根据适用的测试方法获得的平均值, 并受正常生产波动的影响。 产品参数如有更改,恕不另行通知。 如需了解更多产品信息,请联系名冠。

The disclosed performances and measured values of the product in this document are not legally binding statements of product quality. These performances and values will not form part of the contract. They represent average values obtained at the time of manufacture according to applicable test methods and are subject to normal manufacturing variations. The products properties are subject to change without prior notice. Please contact Mingguan for more information.

